


## EBB SB2240\2209 CAN V1.0 BUILD GUIDE

---

VERSION 2023-01-13



Thanks to **CHAOTICLAB** for providing guidance on Voron's official style build guide, and designing the printed part model for EBB SB2240\2209 CAN.

- Highlighted in blue are included in this EBB SB2240\2209 CAN v1.0.
- Highlighted in red are other accessories of the Voron StealthBurner, which are not included in this EBB SB2240\2209 CAN v1.0 and will need to be purchased by yourself.



## Table of Contents

---


### Packing List

---


StealthBurner Body	1
EBB SB0000 CAN v1.0 Overview	1
Turbine Fan	3
Axial Fan	4
PWM Fan	5
LED	6
 ClockWork2	 7
EBB SB2240\2209 CAN v1.0 Overview	7
Install EBB SB2240\2209 CAN v1.0	8
Extruder Motor	10
Thermistor	11
PT100/1000	12
Heater Cartridge	13
 X-Carriage	 14
Proximity Switch	14
X Axis Limit Switch	15
Voron Tap	16
BLTouch	17

StealthBurner Final Assembly	18
CW2 Cable Bridge	19
Fix CAN / USB-C Cable	21
StealthBurner to Mainboard Wiring	23
 Klipper	 24
Compile Firmware	24
Firmware Update (via STM32CubeProgrammer)	25
Firmware Update (via DFU)	28
Firmware Update (via Canboot)	31
CAN bus Configure	34
Klipper Configure	35


PACKING LIST




BIGTREETECH EBB SB2240/2209 CAN V1.0 1pc




BIGTREETECH EBB SB0000 CAN V1.0 1pc




CAN bus Cable 1pc




Crimp Pin  
1.25 mm pitch 40pcs  
3.0 mm pitch 5pcs  
2.54 mm pitch 20pcs




1.25 mm Pitch Pin Connector Housing  
2Way 1pc  
3Way 2pcs  
4Way 2pcs  
5Way 1pc  
8Way 1pc




2.54mm Pitch Pin Connector Housing  
1Way 15pcs




3.0 mm Pitch Pin Connector Housing  
2Way 1pc




Jumper Cap 15pcs




Insulated Wire Ferrule 2pcs



Heat Sink 1pc




M3 x 10 Button Head Cap Screw (BHCS) 4pcs





### WIRE TERMINAL

EBB SB0000 CAN v1.0 use 2.54 pitch DuPont connector. Therefore, all fans and LED lights on StealthBurner Body should be 2.54 pitch DuPont connector.






### TIPS

Install 5010 turbine fan, 4010 axial fan, and LED lamp before installing EBB SB0000 CAN v1.0.




## FAN VOLTAGE


All fans on the EBB SB0000 CAN v1.0 support multi voltage selection, as shown in the figure, and jumper caps are inserted or removed according to the actual voltage used.



Fan Voltage: 5V




Fan Voltage: 12V



Fan Voltage: 24V



## FAN VOLTAGE

All fans on the EBB SB0000 CAN v1.0 support multi voltage selection, as shown in the figure, and jumper caps are inserted or removed according to the actual voltage used.




## PWM FAN


You can also use PWM fan on EBB SB0000 CAN v1.0. As shown in the figure, it contains a 4 pins PWM fan header (2.54 pitch and 4 pins DuPont connector).



Fan Voltage: 5V



Fan Voltage: 12V





Fan Voltage: 24V


## FAN VOLTAGE



All fans on the EBB SB0000 CAN v1.0 support multi voltage selection, as shown in the figure, and jumper caps are inserted or removed according to the actual voltage used.
















**TIPS**

When EBB SB2240\2209 CAN v1.0 is used on StealthBurner, the minimum wire length of the motor is 76mm.


However, it is recommended to leave some allowance for wiring and assembly, such as a wire length of 100mm or 110mm.



PH1.25-PIN



**TIPS**

When EBB SB2240\2209 CAN v1.0 is used on StealthBurner, the minimum wire length of the thermistor is 103mm. However, it is recommended to leave some allowance for wiring and assembly, such as a wire length of 120mm or 130mm.



### TIPS


EBB SB2240\2209 CAN v1.0 is compatible with 2-wire and 4-wire PT100 or PT1000, but not 3-wire PT100 or PT000. As shown in the figure, wire and adjust the dial switch according to the actual model. And the terminals are PH1.25.





MX3.0-2PIN

## TIPS

When EBB SB2240\2209 CAN v1.0 is used on StealthBurner, the minimum wire length of the heater cartridge is 130mm. However, it is recommended to leave some allowance for wiring and assembly, such as a wire length of 150mm or 160mm.








## END-STOP SWITCHES FOR X


End-stops are wired in a "Normally Closed" configuration. On microswitches those are the 2 outer terminals indicated by C and NC.


## TIPS


When EBB SB2240\2209 CAN v1.0 is used on StealthBurner, the minimum wire length of the X Axis Limit Switch is 145mm. However, it is recommended to leave some allowance for wiring and assembly, such as a wire length of 165mm or 175mm.



**TIPS**


When EBB SB2240\2209 CAN v1.0 is used on StealthBurner, the minimum wire length of the X Axis Limit Switch is 150mm, Tap cable is 70mm. However, it is recommended to leave some allowance for wiring and assembly, such as a wire length of 170mm or 180mm for X Axis Limit Switch and 100mm or 110mm for Tap.














## TIPS

The CW2 cable bridge is a custom printed part that can be downloaded directly from our GitHub repository, in EBB\EBB SB2240\_2209 CAN\Custom Printed Parts.



### TIPS


The printed part for CAN cable is a custom printed part that can be downloaded directly from our GitHub repository, in EBB\EBB SB2240\_2209 CAN\Custom Printed Parts, as well as the printed part for USB-C cable.



### CABLE CLIP

The cable clip printed part can be downloaded from our GitHub repository, in EBB\EBB SB2240\_2209 CAN\Custom Printed Parts, or you can use zip ties instead.





1.) After SSH is successfully connected to Raspberry Pi, run

```
cd ~/klipper/
make menuconfig
```

Compile the firmware with the following configuration (if the options below are not available, please update your Klipper source code to the newest version).

[\*] Enable extra low-level configuration options

Micro-controller Architecture (STMicroelectronics STM32) ---->

Processor model (STM32G0B1) ---->

If you do not use CanBoot

Bootloader offset (No bootloader) ---->

If CanBoot is used

Bootloader offset (8KiB bootloader) ---->


Clock Reference (8 MHz crystal) ---->

If USB communication on Type-C is used

Communication interface (USB (on PA11/PA12)) ---->


If CAN-Bus communication is used

Communication interface (CAN bus (on PB0/PB1)) ---->  
(1000000) CAN bus speed




2.) Press 'q' to exit, and "Yes" when asked to save the configuration.

3.) Run **make** to compile firmware, "klipper. bin" file will be generated in **home/pi/klipper/out** folder when **make** is finished, download it onto your computer using the SSH application.




Update directly through computer.


1.Open the STM32CubeProgrammer and select the firmware to download (klipper. bin).




2.Press and hold the **Boot** button, and then click the **Reset** button to enter the DFU mode.



3. Click the **Refresh** icon in STM32CubeProgrammer until the Port changes from "No DFU d..." to "USB1", and then click **Connect** to connect to the chip.




4. After the connection is successful, **Connect** will become **Disconnect**, and then click **Download** to start downloading the program. After the download is completed, a pop-up window of "File download complete" will appear, indicating that the writing is successful.



Raspberry Pi or CB1 update via DFU.

1. Press and hold the **Boot** button, and then click the **Reset** button to enter the DFU mode.



2.Enter in the SSH terminal command line

```
lsusb
```

Query DFU device ID

```
pi@fluiddpi:~$ lsusb
Bus 001 Device 005: ID 0483:df11 STHicroolactronics STM Device in DFU Mode
Bus 001 Device 004: ID 1d50:6061 OpenMoko, Inc. Geschwister Schneider CAN adapter
Bus 001 Device 003: ID 0424:0c00 Microchip Technology, Inc. ( formerly SMSC ) SMC9512/9514 Fast Ethernet Adapter
Bus 001 Device 002: ID 0424:9514 Microchip Technology, Inc. ( formerly SMSC ) SMC9514 Hub
Bus 001 Device 001: ID 1d6b:0002 Linux Foundation 2.0 root hub
pi@fluiddpi:~$
```

3.Run:

```
cd klipper
```

to enter to the klipper directory, then run the following command to write the firmware:

```
make flash FLASH_DEVICE=0483:df11
```

Note: Replace 0483: df11 with the actual device ID found in the previous step.

4. The prompt " **File downloaded successfully** " indicates that the writing is completed.  
After the writing is completed, there will be an error message: **dfu-util: Error during download get\_status**, just ignore it.

5. After the firmware is written, run

```
ls /dev/serial/by id/
```

to query the serial ID of the device (this ID can only be found in the USB communication mode, and this step is ignored in CANBus mode).

6. If USB communication is used, after the first writing, it is not necessary to manually press the Boot and Reset buttons to enter the DFU mode when updating again.

You can directly enter

```
make flash FLASH_DEVICE=/dev/serial/by-id/usb-Klipper_stm32g0b1xx_0F0033000C504B4633373520-if00
```

to write the firmware (Note: replace /dev/serial/by id/xxx with the actual ID found in the previous step).

7. The prompt " **File downloaded successfully** " indicates that the writing is completed.

After the writing is completed, there will be an error message: **dfu-util: Error during download get\_status**, just ignore it.



Raspberry Pi or CB1 updated via CanBoot.

Refer to the instructions here to download the CanBoot project

<https://github.com/Arksine/CanBoot>

1.Run:

```
cd ~
```

to enter the home directory, then run:

```
git clone https://github.com/Arksine/CanBoot
```

to download CanBoot project.

run:

```
cd CanBoot
```

to enter the CanBoot directory.

2.Run:

```
make menuconfig
```


and configure according to the following figure

```
(top)
CanBoot Configuration V0.0.1-33-p88e208a
Micro-controller Architecture (STMicroelectronics STM32) --->
  Processor model (STM32G0B1) --->
  Build CanBoot deployment application (Do not build) --->
  Clock Reference (8 MHz crystal) --->
  Communication interface (CAN bus (on PB0/PB1)) --->
  Application start offset (8KiB offset) --->
(1000000) CAN bus speed
() GPIO pins to set on bootloader entry
[*] Support bootloader entry on rapid double click of reset button
[ ] Enable bootloader entry on button (or gpio) state
[*] Enable Status LED
(PA13) Status LED GPIO Pin
```

## 3.Run

**make**

to compile firmware, 'canboot.bin' file will be generated in `home/pi/klipper/out` folder when **make** is finished, download it onto your computer using the SSH application.



4.Use STM32CubeProgrammer software to write 'canboot. bin' to the chip.

## 5.Run:

**cd ~/CanBoot/scripts**

then run:

**python3 flash\_can.py -i can0 -q**

to query the canbus ID (connect the CAN cable and power it on in advance), as shown in the figure on the right, the UUID of the device has been found.

```

biqu@BTT-CB1:~/CanBoot/scripts$ python3 flash_can.py -i can0 -q
Resetting all bootloader node IDs...
Checking for canboot nodes
Detected UUID: be69315a613c, Application: CanBoot
Query Complete
biqu@BTT-CB1:~/CanBoot/scripts$
  
```

6.Run:

```
python3 flash_can.py -i can0 -f ~/klipper/out/klipper.bin -u be69315a613c
```

The be69315a613c is replaced with the actual UUID. Note: klipper.bin needs to be made in advance, and the application start offset of CanBoot is 8KiB offset, so Klipper's menuconfig Bootloader offset should also be 8KiB bootloader, as shown in the following figure.

```
biqu@BTT-CB1:~/CanBoot/scripts$ python3 flash_can.py -i can0 -f ~/klipper/out/klipper.bin -u be69315a613c
Sending bootloader jump command...
Resetting all bootloader node IDs...
Checking for canboot nodes...
Detected UUID: be69315a613c, Application: CanBoot
Attempting to connect to bootloader
CanBoot Connected
Protocol Version: 1.0.0
Block Size: 64 bytes
Application Start: 0x8002000
MCU type: stm32g0b1xx
Verifying canbus connection
Flashing '/home/biqu/klipper/out/klipper.bin'...

[#####]

Write complete: 13 pages
Verifying (block count = 414)...

[#####]

Verification Complete: SHA = C3B1F96A8FCE706587BF4A9119D95D80465875A3
CAN Flash Success
biqu@BTT-CB1:~/CanBoot/scripts$
```


6.Run:

```
python3 flash_can.py -i can0 -q
```

to query. At this time, the Application changes from CanBoot to Klipper, indicating that Klipper has been running normally.

```
biqu@BTT-CB1:~/CanBoot/scripts$ python3 flash_can.py -i can0 -q
Resetting all bootloader node IDs...
Checking for canboot nodes...
Detected UUID: be69315a613c, Application: Klipper
Query Complete
biqu@BTT-CB1:~/CanBoot/scripts$
```

Used with BIGTREETECH U2C module.



1. Enter the command

```
sudo nano /etc/network/interfaces.d/can0
```

in the SSH terminal and execute

```
allow-hotplug can0
iface can0 can static
    bitrate 1000000
up ifconfig $IFACE txqueuelen 1024
```

Set the CAN-BUS speed to 1M (it must be consistent with the speed set in the firmware **(1000000) CAN bus speed**), save (Ctrl+S) and exit (Ctrl+X) after modification, and enter

```
sudo reboot
```

to restart Raspberry Pi.

2. Each device on CAN bus will generate a canbus\_uuid according to the UID of MCU, to find each microcontroller device ID, make sure the hardware is powered on and wired correctly, and then run:

```
~/klippy-env/bin/python ~/klipper/scripts/canbus_query.py can0
```


3. If an uninitialized CAN device is detected, the above command will report the device's canbus\_uuid.

```
Found canbus_uuid=0e0d81e4210c
```


4. If Klipper has been running normally and connected to this device, then canbus\_uuid will not be reported, which is normal.

1. Enter Raspberry Pi IP address into your browser, and find the reference config for the motherboard in the directory shown below, if there is no such config available, update your Klipper source code to the newest version or download it from GitHub:

<https://github.com/bigtreetech/EBB>



2. Upload the configuration file of the motherboard to Configuration Files.



3. Add the configuration of this motherboard in the "printer.cfg" file:

```
[include sample-bigtreetech-ebb-sb-canbus-v1.0.cfg]
```

X printer.cfg

11

12

13

```
[include sample-bigtreetech-ebb-sb-canbus-v1.0.cfg]
```

4. Enter the correct ID (USB serial or canbus).

X sample-bigtreetech-ebb-sb-canbus-v1.0.cfg

8

9

10

```
[mcu EBBCan]
```

```
serial: /dev/serial/by-id/usb-Klipper_firmware_12345-if00
```

```
#canbus_uuid: 0e0d81e4210c
```

5. Configure the module's specific functions according to

<https://www.klipper3d.org/Overview.html>

---

Website

[www.bigtree-tech.com](http://www.bigtree-tech.com)

GitHub

[www.github.com/bigtreotech](https://www.github.com/bigtreotech)

Discord

[www.discord.gg/5jdwbYYZuv](https://www.discord.gg/5jdwbYYZuv)

---

